## WHC623E14X



## Freestanding wall chimney cooker hood



Polyurethane filter



LedLight

Re-circulating hoods

🖌 Noise level

Wall mounted cooker hood Venting with air extraction or recirculation Energy class: C Material of housing/chimney: stainless steel / stainless steel Colour of housing/chimney: stainless steel / stainless steel Lightning efficiency class: A Grease filtering efficiency class: A Fluid dynamic efficiency class: E Maximum extraction rate by extraction operation: 408 m3/h Maximum extraction rate by recirculation operation: 300 m<sup>3</sup>/h Venting tube diameter: 15 cm Air flow by extraction version, step 1: 250 m3/h Air flow by extraction version, step 2: 348 m3/h Air flow by extraction version, step 3: 408 m3/h Mechanic control Control setting: Button control Number of speed positions: 3 Lamp type: LED On/off light switch Number of lights: 2 Power of lights: 6 W Filter material: Washable aluminium with polyurethane foam Coal filter code (optional as separate purchase): 315275 Number of filters: 2 Motor type: Capacitor motor Number of motors: 1 No return airflow flap: 150 mm Max. noise level: 65 dB(A)re 1 pW Height: 250 mm Min. height of the chimney: 545 mm Max. height of the chimney: 875 mm Annual energy consumption: 61.5 kWh Dimensions (W×H×D): 60 × 25 × 50 cm Dimensions of packed product (W×H×D): 64.5 × 63.7 × 36.5 cm Net weight: 8.6 kg Gross weight: 11.3 kg Connected load: 126 W Nominal current of fuse: 10 amp Product code: 514489

EAN code: 3838942071997

